

# SUB-JET 1902



**2-Head High Speed  
Digital Sublimation Printer**

**I3200 - A1 2H**

**TOP SPEED 80 m<sup>2</sup>/h**

Sublimation Ink

**C M Y K**

# SUB-JET 1902

## 2-Heads High Speed Digital Sublimation Printer

### Technical Characteristics

- Original i3200 print head, more durable and stable.
- Felt roller to ensure smoother paper feeding.
- 2 pcs heads configuration, higher productivity.
- Professional color management software, more accurate output color.
- Bold structure brings more stable long-term printing.
- Fully sealed drying system and mute fans reduce noise a lot.
- State-of-art industrial design concept, strong body.

### Technical Specifications

Model	SUB-JET 1902	
Print Head	Two I3200 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	72 in.(1830 mm)
	Thickness	Maximum 39 mil(1 mm)
	Maximum Media Load	500m
Printing Width	70.8 in.(1800 mm)	
Ink Cartridges	Type	Dye Sublimation Ink
	Color	4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 3600 dpi	
Rip Software	Ergosoft / Neostampa	
Printing Speed	1pass(360x1200dpi): 80m <sup>2</sup> /h	
	2pass(360x2400dpi): 40m <sup>2</sup> /h	
Media Heating System	Intergated post heater & Infrared Dryer & Fan system	
Interface	USB 3.0	
Power Supply	AC 220V ± 10%. 50/60 HZ	
Environment	Power on	Temperature: 59 °F to 90 °F [15°C to 32°C] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 °F to 104 °F [5°C to 40°C] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	

Machine Dimension: L2930mm\*W830mm\*H1600mm

Machine Box: L3080mm\*W840mm\*H750mm

Net Weight: 272KG

Rated current: 32A/554

Rated voltage: AC 220-240 V/100-120 V

Rated power: 230W+2400W



Junbo media roll maximum 1000m media load.



Double high-precision mute rail.



Rear media balance bar



Integrated IR & cooling fan system.

