



JLD-I 多口數機

Double Jersey Multi-Feeder Circular Knitting Machine

多口數雙面機為專用的平布機，專為需要產量高的廠商所研發的機種。菱角座為上二段下二段的設計，機台設計符合簡單化，客戶操作容易。

This machine is designed for High Production with special emphasis to a very High Quality in Plain Interlock Fabric. Cam block designed for 2 tracks on dial and 2 tracks on cylinder, and the operation is very easy. This machine is equipped with 3 Feeders per Diametrical Inch.

規格 Specification

規格 Specification	針距 Gauge / 針號 Needle no. 19 ~ 22G	針距 Gauge / 針號 Needle no. 24 ~ 30G	轉速 RPM
30"x90F/84F	上針用65. 48 下針用83. 48	上針用65. 41 下針用83. 41	22-25RPM
32"x96F/90F			
34"x102F/96F			
36"x108F/100F			
38"x114F/106F			
40"x120F/112F			

機種優點 Advantage of JLD-I

- 採中央調控，易於調整布目及碼重。(專利號碼：200586)
- 同步喂紗嘴的設計，可同步上下左右調整喂紗棒。(專利號碼：283855)
- 速度可達25RPM，例：30□x90Fx24~28G，75/D 化纖，190公斤/24小時，產量高。
- 所織布面平穩、品質佳。
- 機器採精密的加工程式，尤其菱角及菱角座與織針的設計，非常精準。
- 馬達採7.5HP，馬力足，機台運轉快。
- Central stitch adjustment system, easy for adjusting G.S.M. & arm Loop Size. (Patent No.: 200586)
- Synchronized yarn feeder system, for easier Yarn Feeder Positioning / Adjustment. (Patent No. 283855)
- Machines are able to run upto 30 RPM but with lower decibel and high production. For example, 30□x 90F x 24~28G，75/D polyester yarn，190 kgs per 24 hours.
- Neat fabric quality.
- High Precision Procedure: High Precision Quality especially for Cams, Cams Box etc..
- 7.5HP motor capacity enables to run the machine in good speed.

生產量及轉速 Production & Speed

規格specification	紗 Yarn	19G 產量 Production	24G產量 Production	28G產量 Production	轉速 RPM
JLD-I 30-2x2 30"x90F	POLY 75/D		190-210KGS	220-240KGS	25RPM
	COTTON C/30 (棉)			500KGS	25RPM
JLD-I 32-2x2 32"x96F	POLY 75/D		190-210KGS	220-240KGS	25RPM
	COTTON C/30 (棉)			500KGS	25RPM
JLD-I 34-2x2 34"x102F	POLY 75/D		250-270KGS	275-300KGS	22-25RPM
	POLY 150/D	320-360KGS		275-300KGS	22-25RPM
	COTTON C/30 (棉)	380-420KGS		500-600KGS	22-25RPM
JLD-I 36-2x2 36"x108F	POLY 75/D		250-270KGS		22-25RPM
	POLY 150/D	320-360KGS			22-25RPM
	COTTON C/30 (棉)	380-420KGS	520-560KGS		22-25RPM